



<b>Specification</b>	Aluminum air termination mast multi-part with 3-leg support QR System made of stainl. steel. With 3 threaded pieces made of stainl. steel. Height of the mast: 8,0m. Weight: 30 kg; Systemweight: 183 kg For wind speed zones III – IV For ground category III- IV (max. gust speed 175 km/h)
<b>Article No.</b>	<b>QR 00 07</b>

Customs tariff No.: 85389099

**Transportlength: 3,0m**

**The mast can be erected  
with 1 person  
WITHOUT a crane !**



Description	Ø	Material	Length	Wind speed zone	Remarks
Mast main tube 1	40,0mm x 5,0mm	Aluminium tube	3,00m	Wind speed zone III-IV (accord. to Euro Code 1 as well as DIN EN 1991 and DIN EN 1993. At 1,5-fold safety). Max. gust speed 175 km/h. Applicable for building heights below 40m and area heights below 600m above NN. Higher buildings or areas as well as icing and self-oscillation are to be considered. separately if necessary.	1. All connections are made of stainless steel V2A. 2. The concrete bases and the respective protective pads are not part of the product. 3. System-weight including the concrete bases: 183 kg. 4. Surface loading rate: 43,6 kg/m² 5. Slope adjustment up to 5° is possible. 6. Pack size: 3000mm long and 200mmØ Weight: 30 kg. 7. Weight of the mast 9,5kg. 8. Weight of the stand 18kg.
Mast main tube 2	30,0mm x 5,0mm	Aluminium tube	1,50m		
Mast tip	1,5m 20mm, 1m 12mm	Aluminium rods	2,50m		
Stand segments		Stainless steel.4301	Support segments: 1525mm Foot segments: 1100mm		
Stand central tube	45,0mm x 2,0 mm	Edelstahlrohr 1.4301	1150 mm		