

	Pyramid holdfast with bottom		DIN EN 6256	1-4:	
Specification	roofs, filled with concrete, to s conductor. Made of polyethy			ng of holders to structures covered	
	Weight: 1 kg	ielie. Diack.		er, membrane and gravel roofs is not	
Article No.	45 03 16			e present standard due to the types which are used on modern	
			construction		
				Customs tariff No.: 85389099	
)		
		S)))		
	- É				
				A.	
/					
(Ň		
Ň					
	T				
	Тор		Bottom		
		Concrete filling:		auiding ⁸	
		Frost proof Euro Norm XF2		- 105e Wille 9	
		T			
		Concrete filling: Frost proof Euro Norm XF2			
				a de la companya de la compa	
	140			4	
	Side	PoHS2 (Guidalina 201	Cutt	(Regulation (EG) No.1907/2006): The	
Description		substance-requiremen		irements of this regulations are observed by	
Weight		this product.			
		_			
Input		8 mm conductor			
Material of the holdfast		ID-PE black	No halogon	s LIV-stabilized and cold	
		LD-PE, black. No halogens, UV-stabilized and cold			
		impact resist	ant.		
Material of the bottom		Polypropylene, black. No halogens.			
Concrete		1 kg frost-resistant concrete.			